





স TRANSPORTATION

Airport entrances and perimeters, air cargo, and checkpoint technology.

PORTS & BORDERS

Border control, sea ports, and other large cargo sectors.

CRITICAL INFRASTRUCTURE

Access control for prisons, courthouses, mailrooms, hotel entrances and military bases.

Designed for high-threat security, the XIS-100XDV is a dual 101.6 cm x 101.6 cm (40.0" x 40.0"). The XIS-100XDV is wellsuited for airports, military and government sites.

A ANTRO

Boasting two x-ray generators, the XIS-100XDV produces two screening perspectives and allows operators to manipulate each independently. Thus, the XIS-100XDV enhances operators ability to identify potential security threats with increased accuracy and speed.

Combined with dual view technology and Astrophysics software, the XIS-100XDV is the ultimate solution for large object screening at inspection sites requiring heightened security protection.

All Astrophysics X-ray Inspection Systems are equipped with

An exclusive Astrophysics option is our 6 Color Imaging, which view X-Ray Inspection System with a generous tunnel size of enables operators to view screened objects in 6 colors, each color correlating to a specific range of Atomic Z-Numbers. 6 Color Imaging enables operators to achieve optimal material identification which improves throughputs.

> Astrophysics is committed to providing quality products and services nationwide. We listen to our customers and offer cus tomizations and order flexibility based on their needs.

> Backed by a team of engineers from our City of Industry, California center of excellence headquarters, Astrophysics designs cutting-edge X-ray screening technology for detect ing weapons and contraband for transportation, ports, bor ders, critical infrastructure and other industries that present security risks.

Real-Time Diagnostics, a unique Astrophysics feature whichAstrophysics is headquartered in the United States and main allows users to monitor system health. This software was spetains a global presence with service delivery worldwide. cifically engineered to save you valuable time and money. Astrophysics is committed to global safety and is proud to If requested, Astrophysics would also be able to connect to present this new age of screening security—driving the indus your system and troubleshoot any issues remotely. try into the technology of tomorrow.



40.0" x 40.0"

123.5" x 68.4" x 77.0"

130.0" x 77.0" x 89.0"

76.0 cm (30.0") from Floor

1435 kg (3165 lbs)

1600 kg (3525 lbs)

313.4 cm x 173.4 cm x 195.9 cm

330.2 cm x 194.3 cm x 225.0 cm

23 cm/s (45 ft/min) Forward or Reverse

40 AWG Typical, 38 AWG Standard 1.0 mm Horizontal, 1.3 mm Vertical

39 mm Typical, 37 mm Standard

Dual 180kV, Operating at 165kV

Sealed Di-Electric Oil Bath with Forced Air 100%, No Warm-Up Procedure Required

Diagonally Upward, Horizontally Sideward 4736 Channels in an L-Shaped Array

Dual 1.2 mA

Intel® Core i5

1 GB Video Card

Windows® OS

500 GB HDD, 120 GB SSD

Uninterruptible Power Supply

Dual 19" LCD Color Monitors

0°C - 40°C \ 32°F - 104°F

-20°C - 60°C \ -4°F - 140°F Up to 95% Non-Condensing

1600 x 1200; 24 Bit/Pixel Color

(Computer Operation - 20 Minute)

110VAC±10%, 50/60Hz, 20 Amp Max

220VAC ±10%, 50/60Hz, 15 Amp Max

4 GB RAM

24 Visible Levels, 4096 Gray Level Guaranteed up to ISO 1600 (33DIN)

GENERAL SPECIFICATIONS 101.6 cm x 101.6 cm

- Tunnel Opening: $(W \times H)$
- Dimension²s $(L \times W \times H)$
- Shipping Dimensions $(L \times W \times H)$
- Net Weight:
- Shipping Weight
- Conveyor Speed:
- · Conveyor Height:
- Conveyor Capacity:

TECHNICAL

- Wire Resolution:
- Spatial Resolution:
- Steel Penetration
- Contrast Sensitivity:
- Film Safety:

X-RAY GENERATOR

- Voltage:
- Tube Current:
- Cooling:
- Duty Cycle:
- Beam Direction:
- Detector:

COMPUTER

- Processor:
- Memory:
- Storage:
- Video Card:
- Platform:
- Backup:

VIDEO

- Display Type:
- Display Resolution:

ENVIRONMENTAL

- Operating Temperature:
- Storage Temperature:
- Humidity:

ELECTRICAL

• Power Requirements:

HEALTH AND SAFETY

- Compliant with USFDA, Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40)
- Typical radiation leakage is less than 0.1 mR/hr (Leakage less than 0.5 mR/hr permitter adiation Meter by the Federal Standard)



¹ As tested on Astrophysics Inc. Test Piece.

²Weight and dimensions of the system may vary depending on customization.

³ Optional features may affect lead time price, and weight of XIS-100XDV. Please contact your Astrophysics Sales Representative for more information. Due to continued product research and development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice.

195.9 cm 200 kg (440 lbs) Evenly Distributed Load 8 313.4 cm

STANDARD FEATURES

- 6 Color Imaging
- 9 Quadrant Zoom
- Atomic Z-Number Measurement
- Auto Image Archiving (150,000)
- Baggage Counter
- · Color and Black/ White Imaging
- Continuous Scanning
- Continuous Zoom up to 64x
- Vertical Zoom Panning
- Geometric Image Distortion Correction
- High Penetration Function
- Heavy Duty Roller Casters
- Image Annotation

OPTIONAL FEATURES

- Custom Paint
- Density Alert
- Extended Entry/ Exit Roller Tables (50 cm Increments)
- Footmat Operator Interlock
- Image Analysis Program (IAP)
- Larger Heavy Duty Casters
- Local Language Support
- Polar Kit
- Remote Workstation Configuration Screener Assist Software
- Sloped Conveyor
- Test Case
- Threat Image Protection (TIP) Software Tropical Kit
- Wireless Barcode Scanning

Material Discrimination

- Multi-Tier Accessibility
- Network Ready
- Organic/ Inorganic Imaging
- Operator Training Program (OTP)
- Picture Perfect
- Print Image Capable
- Pseudo Color
- Real-Time Image Manipulation
- Real-Time Self Diagnostics
- Reverse Monochrome
- Save Image (RGB)
- Image Review



Телефон: +7(495)215-54-75; +7(800)100-54-75; E-mail: sales@pro-spec.ru; www.pro-spec.ru

173.4 cm

<u>XIS-100XDV</u>

